



SPECIFICATION

Surface Mounted Waste Bin shall have a capacity of 45.4 litres. Unit shall be fabricated of alloy 18-8 stainless steel, grade 304, 22 gauge with No. 4 satin finish and be protected during shipment with a PVC film easily removable after installation. Bin shall have no exposed fastening devices or spot welded seams and shall have front outer vertical edges rounded to 13mm radius. Bin shall have four (4) interior hooks for hanging a reusable heavy gauge clear vinyl bag with reinforced edges and grommets. Bin shall be mounted to wall through key hole slots on back of unit and be theft resistant after installation of concealed locking screw.

INSTALLATION

Hang unit on pre-installed four (4) screws (supplied by others) on wall through the mounting 'key hole' slots. Install and fasten theft-resistant screw (supplied by others) to wall through middle top hole of bin. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

OPERATION

User deposits waste material. Maintenance schedule determines trash removal cycle. Unit is emptied by removing collection liner bag to empty into appropriate bulk collection bin. Liner is washable and reusable and replacements are available should they be required.

WARRANTY

One year.

Surface Mounted Waste Bin shall be Model No. 10-0826 as supplied by ASI JD MacDonald.

