



FEATURES

Recessed Parallel Full SS Baby Change Station includes a concealed damped gas spring mechanism for smooth, safe and effortless opening and closing using one hand. Two-part child protection safety-strap and cam buckle, adjustable with one hand and two heavy-duty bag hooks. Unit provides a bed-liner dispenser and a multi-fold towel dispenser. Graphic and instructions in four languages on interior back. The strength of the supporting wall and hardware must be adequate to support the rated load. Antimicrobial treated material used for internal back, bed, dispenser doors, strap and molded mounting hole covers.

INSTALLATION DETAILS

Provide rough wall opening 870 wide x 578 high x 95 minimum depth from face of finished wall. Mount unit in wall opening using either four №10 x 1-1/2" (38) long self-tapping screws through side holes or four 3/8" x 2" (Ø10 x 51) lag screws (or other fasteners appropriate for wall conditions) through mounting holes in rear wall of cabinet. Use washers and snap covers provided.

ROUGH WALL OPENING (RWO)

870(W) x 578(H) x 95(D)

SPECIFICATION

Unit supports a minimum load of 181.4kg when properly installed in accordance with the Installation and Operating Instructions supplied with the unit.

MATERIAL

High density polyethylene body (HDPE) and satin finished 304 stainless steel.

OPTIONS


- Surface Mount unit available (Part No. 10-9013-9)
- Box of 500 liners (Part No: LCR)
- Replacement strap (Part No: 10-9013-32945)

WARRANTY & PRODUCT LIABILITY

ASI JD MacDonald Baby Change Stations are guaranteed against defective materials and faulty workmanship for 5 years from date of purchase, subject to being installed and maintained in accordance with the Installation and Operating Instructions supplied with the unit.

A \$10 million product liability insurance policy is maintained on all baby change stations.

Recessed Baby Change Station Full Stainless Steel Parallel shall be Model No. 10-9013 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald accessible compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

ALL DIM'S
INCH [MM]

